


low forward voltage

low leakage current

smaller package outline

cost reduction


3G




Lighting




Consumer



Mobility



Energy



Industrial

3G Schottky


Redefined Solution

3rd Generation Technology by Diotec


Power Saving

Rugged Design

State-of-the-Art Performance



Standard Technology



3G Schottky Technology

Miniaturizing Chip Design
Smaller, Stronger, Smarter...

State-of-the-Art Performance

Typical Usage

Output Rectifier
Polarity Protection
LED Driver
OR-ing Diodes
Battery Charger
Free-Wheeling Diodes

Features/Benefits

Low Forward Voltage
Low Reverse Current
Low Power Losses
High ESD Robustness
Energy Savings
Less Heat Generation

3G Schottky Diodes for Consumer Applications

Part Number	V _{RRM} [V]	I _{FAV} [A]	V _F [V]	@ I _F /T _J	V _F [V]	@ I _F /T _J	I _R [μA]	@ V _R /T _J	C _j [pF]	Package
SGL34-40*	40	0.5	0.40	0.5A/25°C	0.35	0.5A/100°C	10	40V/25°C	55	DO-213AA/MiniMelf
SGL1-40*	40	1	0.45	1A/25°C	0.40	1A/100°C	10	40V/25°C	55	DO-213AA/MiniMelf
SGL15-40*	40	1.5	0.50	1.5A/25°C	0.45	1.5A/100°C	10	40V/25°C	55	DO-213AA/MiniMelf
SMS140*	40	1	0.38	1A/25°C	0.32	1A/100°C	40	40V/25°C	120	DO-213AB/Melf
SMS240*	40	2	0.42	2A/25°C	0.37	2A/100°C	40	40V/25°C	120	DO-213AB/Melf
SMS340*	40	3	0.45	3A/25°C	0.40	3A/100°C	40	40V/25°C	120	DO-213AB/Melf
SL32SMA-3G	20	3	0.43	3A/25°C	0.37	3A/100°C	15	20V/25°C	90	DO-214AC/SMA
SL34SMA-3G	40	3	0.43	3A/25°C	0.37	3A/100°C	60	40V/25°C	90	DO-214AC/SMA
SK34SMA-3G	40	3	0.48	3A/25°C	0.43	3A/100°C	30	40V/25°C	90	DO-214AC/SMA
SL52-3G	20	5	0.42	5A/25°C	0.37	5A/100°C	20	20V/25°C	90	DO-214AA/SMB
SL54-3G	40	5	0.42	5A/25°C	0.37	5A/100°C	150	40V/25°C	320	DO-214AA/SMB
SK54-3G	40	5	0.47	5A/25°C	0.42	5A/100°C	20	40V/25°C	340	DO-214AA/SMB
SL82-3G	20	8	0.47	5A/25°C	0.39	5A/100°C	20	20V/25°C	320	DO-214AB/SMC
SL84-3G	40	8	0.47	8A/25°C	0.39	8A/100°C	150	40V/25°C	320	DO-214AB/SMC
SK84-3G	40	8	0.51	8A/25°C	0.44	8A/100°C	30	40V/25°C	340	DO-214AB/SMC
PPS1045-3G	45	10	0.48	10A/25°C	0.42	10A/100°C	70	45V/25°C	510	TO-277B/PowerSMD
SK1040D2-3G	40	10	0.48	10A/25°C	0.42	10A/100°C	60	40V/25°C	510	TO-263AB/D ² PAK
SK1045D2-3G	45	10	0.48	10A/25°C	0.42	10A/100°C	70	45V/25°C	510	TO-263AB/D ² PAK
SBT1045-3G	45	10	0.48	10A/25°C	0.42	10A/100°C	70	45V/25°C	510	TO-220AC
PPS1545-3G	45	15	0.52	15A/25°C	0.43	15A/100°C	80	45V/25°C	720	TO-277B/PowerSMD
SK1545YD2-3G	45	15	0.52	15A/25°C	0.43	15A/100°C	80	45V/25°C	720	TO-263AB/D ² PAK

*coming 2Q 2019