

low forward voltage

low leakage current

smaller package outline

cost reduction


3G




Lighting




Consumer



Mobility



Energy



Industrial

3G Schottky


Redefined Solution

3rd Generation Technology by Diotec

Power Saving

Rugged Design

State-of-the-Art Performance



Standard Technology

3G Schottky Technology

Miniaturizing Chip Design
Smaller, Stronger, Smarter...

State-of-the-Art Performance

Typical Usage

Output Rectifier
Power Supplies
DC/DC Converter
Battery Charger
Polarity Protection

Free-Wheeling Diodes
LED Driver
OR-ing Diodes

Features/Benefits

Low Forward Voltage
Low Reverse Current
Low Power Losses
High ESD Robustness
Energy Savings

3G Schottky Diodes for Industrial Applications

Part Number	V _{RRM} [V]	I _{FAV} [A]	V _F [V]	@ I _F /T _J	V _F [V]	@ I _F /T _J	I _R [μA]	@ V _R /T _J	C _J [pF]	Package
SGL34-40*	40	0.5	0.40	0.5A/25°C	0.35	0.5A/100°C	10	40V/25°C	55	DO-213AA/MiniMelf
SGL1-40*	40	1	0.45	1A/25°C	0.40	1A/100°C	10	40V/25°C	55	DO-213AA/MiniMelf
SGL15-40*	40	1.5	0.50	1.5A/25°C	0.45	1.5A/100°C	10	40V/25°C	55	DO-213AA/MiniMelf
SMS140*	40	1	0.38	1A/25°C	0.32	1A/100°C	40	40V/25°C	120	DO-213AB/Melf
SMS240*	40	2	0.42	2A/25°C	0.37	2A/100°C	40	40V/25°C	120	DO-213AB/Melf
SMS340*	40	3	0.45	3A/25°C	0.40	3A/100°C	40	40V/25°C	120	DO-213AB/Melf
SL32SMA-3G	20	3	0.43	3A/25°C	0.37	3A/100°C	15	20V/25°C	90	DO-214AC/SMA
SL34SMA-3G	40	3	0.43	3A/25°C	0.37	3A/100°C	60	40V/25°C	90	DO-214AC/SMA
SK34SMA-3G	40	3	0.48	3A/25°C	0.43	3A/100°C	30	40V/25°C	90	DO-214AC/SMA
SL52-3G	20	5	0.42	5A/25°C	0.37	5A/100°C	20	20V/25°C	90	DO-214AA/SMB
SL54-3G	40	5	0.42	5A/25°C	0.37	5A/100°C	150	40V/25°C	320	DO-214AA/SMB
SK54-3G	40	5	0.47	5A/25°C	0.42	5A/100°C	20	40V/25°C	340	DO-214AA/SMB
SL82-3G	20	8	0.47	5A/25°C	0.39	5A/100°C	20	20V/25°C	320	DO-214AB/SMC
SL84-3G	40	8	0.47	8A/25°C	0.39	8A/100°C	150	40V/25°C	320	DO-214AB/SMC
SK84-3G	40	8	0.51	8A/25°C	0.44	8A/100°C	30	40V/25°C	340	DO-214AB/SMC
PPS1045-3G	45	10	0.48	10A/25°C	0.42	10A/100°C	70	45V/25°C	510	TO-277B/PowerSMD
SK1045D2-3G	45	10	0.48	10A/25°C	0.42	10A/100°C	70	45V/25°C	510	TO-263AB/D ² PAK
SBT1040-3G	40	10	0.48	10A/25°C	0.42	10A/100°C	60	40V/25°C	510	TO-220AC
SBT1045-3G	45	10	0.48	10A/25°C	0.42	10A/100°C	70	45V/25°C	510	TO-220AC
PPS1545-3G	45	15	0.52	15A/25°C	0.43	15A/100°C	80	45V/25°C	720	TO-277B/PowerSMD
SK1545YD2-3G	45	15	0.52	15A/25°C	0.43	15A/100°C	80	45V/25°C	720	TO-263AB/D ² PAK
SK1845D2-3G	45	18	0.53	18A/25°C	0.44	18A/100°C	80	45V/25°C	720	TO-263AB/D ² PAK
SBT1840-3G	40	18	0.53	18A/25°C	0.44	18A/100°C	70	40V/25°C	720	TO-220AC
SBT1845-3G	45	18	0.53	18A/25°C	0.44	18A/100°C	80	45V/25°C	720	TO-220AC
SK2045YD2-3G	45	20	0.52	20A/25°C	0.43	20A/100°C	80	45V/25°C	720	TO-263AB/D ² PAK
SK2045CD2-3G	45	2x10	0.48	10A/25°C	0.42	10A/100°C	70	45V/25°C	510	TO-263AB/D ² PAK
SK2545YD2-3G	45	25	0.54	25A/25°C	0.49	25A/100°C	60	45V/25°C	800	TO-263AB/D ² PAK
SK3045CD2-3G	45	2x15	0.52	15A/25°C	0.43	15A/100°C	80	45V/25°C	720	TO-263AB/D ² PAK
SK4045CD2-3G	45	2x20	0.52	15A/25°C	0.43	15A/100°C	80	45V/25°C	720	TO-263AB/D ² PAK
SB1240-3G	40	12	0.49	12A/25°C	0.44	12A/100°C	60	40V/25°C	510	-DO-201
SB1540-3G	40	18	0.53	18A/25°C	0.44	18A/100°C	60	40V/25°C	720	D5.4x7.5
155Q045-3G	45	15	0.52	15A/25°C	0.43	15A/100°C	80	45V/25°C	720	D5.4x7.5
SBX2040-3G	40	20	0.52	15A/25°C	0.43	20A/100°C	70	40V/25°C	720	D5.4x7.5 - Low Rth
205Q045-3G	45	20	0.52	15A/25°C	0.43	20A/100°C	80	45V/25°C	720	D5.4x7.5
SBX2540-3G	40	25	0.54	25A/25°C	0.49	25A/100°C	70	40V/25°C	720	D5.4x7.5 - Low Rth
SBX3040-3G	40	30	0.54	30A/25°C	0.49	30A/100°C	50	40V/25°C	720	D5.4x7.5 - Low Rth

*coming 2Q 2019